

General Electric Specification : 48V Basic System Module P4X HV

	HD	UHD	HP			
Battery Capacity @ 1 A Discharge	37	45	39	Ah	+ 2 / - 2	@ 0 cycles
Battery Capacity @ 15 A Discharge	34,5	42	33	Ah	+ 1.5 / - 1.5	@ 0 cycles
Minimal Cycle Life (standard setting)	1000	500	300	#	full cycles	min. 70% rated capacity
Minimal Cycle Life (long life setting)	2000	1000	500	#	full cycles	min. 70% rated capacity
Nominal Voltage	51,1	50,9	50,9	V		
Charge Voltage Limit	58,8	58,8	58,8	V	+ 0.0 / - 0.28	not for long life settings
Nominal Charge Current	15	15	15	A		recommended : "CC" and "CV" model
End of Charge Current Limit	0,5	0,5	0,5	A		advised
Discharge Voltage Limit	43	43	43	V	+/- 1	drive system should shutdown at this Voltage
Nominal Discharge Current	40	40	50	A		
Peak Discharge Current	75	75	120	A		@ T =25°C / 10 sec
Fast Charging	No	No	Yes			
Parallel Switching	No					max 16P
Serie Switching (High Voltage)	100 - 600V					
Certification	UN 38.3					for at least one Cell type
Functional Safety Compliance						design suitable for Certification
Light Electric Vehicle Compliance*						design suitable for Certification
Electric Vehicle compliance*	R100*					design suitable for Certification
Compatibility with NA						design suitable for Certification
Ingress Protection level	IP67					certified design (not tested in production)
						*) Outer Protective Casing required

cleantron[®]
cleantech batteries

Cleantron
Pesetaweg 37 2153 PJ Nieuw Vennep
the Netherlands
+31 (0) 71 887 60 76
www.cleantron.nl

