

P2X LFP

24V

General Electric Specification : 24V Basic Module P2X LFP					
Battery Capacity @ 1 A Discharge	30	Ah	+ 1,5 / - 1,5	@ 0 cycles	
Battery Capacity @ 10 A Discharge	27	Ah	+ 1,5 / - 1,5	@ 0 cycles	
Minimal Cycle Life (standard setting)	1500	#	full cycles	min. 70% rated capacity	
Minimal Cycle Life (long life setting)	2000	#	full cycles	min. 70% rated capacity	
Nominal Voltage	25,7	V			
Charge Voltage Limit	28,8	V	+ 0.0 / - 0.28	not for long life settings	
Nominal Charge Current	50	A		recommended : "CC" and "CV" model	
End of Charge Current Limit	0,5	A		advised	
Discharge Voltage Limit	17	V	+/- 1	drive system should shutdown at this Voltage	
Nominal Discharge Current	80	A			
Peak Discharge Current	120	A		@ T =25°C / 10 sec	
Fast Charging	Yes				
Parallel Switching	Yes (MPC)			max 26 P	
Serie Switching (High Voltage)	No				
Certification	UN 38.3; IEC62133			for at least one Cell type	
Functional Safety Compliance	IEC61508 - SIL 2			design suitable for Certification	
Light Electric Vehicle Compliance*	EN50604-1			design suitable for Certification	
Compatibility with North America	ANSI/CAN/UL/ULC 2271			design suitable for Certification	
Ingress Protection level	IP65				
Dimensions	429 x 266 x 78	mm.			
Weight	12	Kg.			

** MPC = Multi Pack Configuration
Paralles Switching options:

PARALLEL DIS-/CHARGING



Hot Swap
Cycle Intelligent
Charging

Safety
By Redundancy

Benefit
Higher Currents or
Longer Cycle Life

Application
Fixed

SEQUENTIAL DIS-/CHARGING



Hot Swap
Cycle Intelligent
Charging

Safety
By Redundancy

Benefit
Less Packs Needed
Less Chargers Needed

Application
Portable

No rights can be derived from this document.
Please contact Cleantron for more information.

cleantron[®]
cleantech batteries

Pesetaweg 37
2153 PJ Nieuw Vennepe
The Netherlands

+31 (0)71 887 60 76
info@cleantron.nl
www.cleantron.nl