


CLP

48V

General Electric Specification : 48V Compact Light Portable Pack CLP				
Cells Capacity @ 1 A Discharge	40	Ah	+ 1 / - 2	@ 0 cycles
Nominal Capacity @ 10 A Discharge	36	Ah	+ 1 / - 2	@ 0 cycles
Minimal Cycle Life (standard setting)	1000	#	full cycles	min. 70% rated capacity
Minimal Cycle Life (long life setting)	2000	#	full cycles	min. 70% rated capacity
Nominal Voltage	47	V		
Charge Voltage Limit	53	V	+ 0.0 / - 0.28	not for long life settings
Nominal Charge Current	15	A		recommended : "CC" and "CV" model
End of Charge Current Limit	0,5	A		advised
Discharge Voltage Limit	39	V	+/- 1	drive system should shutdown at this Voltage
Nominal Discharge Current	35	A		
Peak Discharge Current	50	A		@ T =25 / 10 sec
Fast Charging	No			
Parallel Switching	Yes (MPC)			max 26 P
Serie Switching (High Voltage)	No			
Certification	UN 38.3; IEC62133			for at least one Cell type
Functional Safety Compliance	IEC61508 - SIL 2			Certified for at least one cell type
Light Electric Vehicle Compliance*	EN50604-1			design suitable for Certification
Compatibility with North America	ANSI/CAN/UL/ULC 2271			design suitable for Certification
Ingress Protection level	IP65			blind mating Docking Station
Dimensions	346 x 292 x 83	mm.		excluding Docking Station
Weight	9	Kg.		
				*) Outer Protective Casing required

** MPC = Multi Pack Configuration
Paralles Switching options:

**PARALLEL
DIS-/CHARGING**




Safety
By Redundancy

Benefit
Higher Currents *or*
Longer Cycle Life

Application
Fixed

Hot Swap
Cycle Intelligent
Charging

**SEQUENTIAL
DIS-/CHARGING**



Safety
By Redundancy

Benefit
Less Packs Needed
Less Chargers Needed

Application
Portable

Hot Swap
Cycle Intelligent
Charging

No rights can be derived from this document.
Please contact Cleantron for more information.

cleantron[®]
cleantech batteries

Pesetaweg 37
2153 PJ Nieuw Vennep
The Netherlands

+31 (0)71 887 60 76
info@cleantron.nl
www.cleantron.nl