

P2P

24V

General Electric Specification : 24V Basic Module P2P					
	HD	UHD			
Cells Capacity @ 1 A Discharge	74	88	Ah	+ 1 / - 2	@ 0 cycles
Nominal Capacity @ 10 A Discharge	70	83	Ah	+ 1 / - 2	@ 0 cycles
Minimal Cycle Life (standard setting)	1000	1000	#	full cycles	min. 70% rated capacity
Minimal Cycle Life (long life setting)	2000	1500	#	full cycles	min. 70% rated capacity
Nominal Voltage	25,2	25,2	V		
Charge Voltage Limit	29,4	29,4	V	+ 0.0 / - 0.28	not for long life settings
Nominal Charge Current	37	37	A		recommended : "CC" and "CV" model
End of Charge Current Limit	0,5	0,5	A		advised
Discharge Voltage Limit	22	22	V	+/- 1	drive system should shutdown at this Voltage
Nominal Discharge Current	50	50	A		
Peak Discharge Current	120	120	A		@ T =25 / 10 sec
Fast Charging	No				
Parallel Switching	Yes (MPC)				typical up to 26 P
Serie Switching (High Voltage)	No				
Certification	UN 38.3; IEC62133				for at least one Cell type
Light Electric Vehicle Compliance*	EN50604-1				design suitable for Certification
Compatibility with North America	ANSI/CAN/UL/ULC 2271				design suitable for Certification
Ingress Protection level	IP44/IP65				IP44 closed Cap; IP65 mated Connector
Dimensions	429 x 266 x 78		mm.		
Weight	12,4		Kg.		

General Electric Specification : 24V Basic Module P2P

** MPC = Multi Pack Configuration
Paralles Switching options:

PARALLEL DIS-/CHARGING



Hot Swap
Cycle Intelligent
Charging

Safety

By Redundancy

Benefit

Higher Currents or
Longer Cycle Life

Application

Fixed

SEQUENTIAL DIS-/CHARGING



Hot Swap
Cycle Intelligent
Charging

Safety

By Redundancy

Benefit

Less Packs Needed
Less Chargers Needed

Application

Portable

No rights can be derived from this document.
Please contact Cleantron for more information.

Pesetaweg 37
2153 PJ Nieuw Vennep
The Netherlands

+31 (0)71 887 60 76
info@cleantron.nl
www.cleantron.nl

cleantron[®]
cleantech batteries