

24V					24V				
P2P					P2X				
NMC	Cap*	I nom	I max	MPC** KWh range	NMC	Cap*	I nom	I max	MPC** KWh range
HD	74Ah	50A	120A	1,9 - 15,2	HD	74Ah	50A	120A	1,9 - 30,4
UHD	88Ah	50A	120A	2,3 - 18,4	UHD	88Ah	50A	120A	2,3 - 36,8

48V					48V				
P4P					P4X				
NMC	Cap*	I nom	I max	MPC** KWh range	NMC	Cap*	I nom	I max	MPC** KWh range
HD	37Ah	50A	120A	1,9 - 15,2	HD	37Ah	50A	120A	1,9 - 30,4
UHD	45Ah	50A	120A	2,3 - 18,4	UHD	45Ah	50A	120A	2,3 - 36,8

48V					48V				
CLP					G4L				
NMC	Cap*	I nom	I max	MPC** KWh range	NMC	Cap*	I nom	I max	MPC** KWh range
	36Ah	35A	50A	1,7 - 13,6		80Ah	80A	180A	4,1 - 24,6

High Voltage					High Voltage Active Cooling				
P4X-HV					P4X-HV-A				
NMC	Cap*	I nom	I max	Serie (HV)	NMC	Cap*	I nom	I max	Serie (HV)
HD	37Ah	50A	120A	100-800V	HD	37Ah	TBD	TBD	100-800V
UHD	45Ah	50A	120A	100-800V	UHD	45Ah	TBD	TBD	100-800V

High Voltage					High Voltage				
GTD-S Module for Tailored Pack					GTD-L Module for Tailored Pack				
LFP	Cap*	I nom	I max	Serie (HV)	LFP	Cap*	I nom	I max	Serie (HV)
	160Ah	TBD	TBD	100-800V		230Ah	TBD	TBD	100-800V

\*) rated Cells Capacity

\*\*) Multi Pack Configuration

**PARALLEL  
DIS-/CHARGING**



Hot Swap  
Cycle Intelligent  
Charging

**Safety**  
By Redundancy  
**Benefit**  
Higher Currents or  
Longer Cycle Life

**Application**  
Fixed

**SEQUENTIAL  
DIS-/CHARGING**



Hot Swap  
Cycle Intelligent  
Charging

**Safety**  
By Redundancy  
**Benefit**  
Less Packs Needed  
Less Chargers Needed

**Application**  
Portable